


SOLID: LINE MIDBAY EMERGENCY LIGHTS



Solid Line Midbay is designed for escape route emergency lighting. The luminaire is completely dust proof and water proof, so it is suitable for example for industrial premises, parking halls, as well as for outdoor use

The Solid luminaire uses long-lasting LEDs as its light source.

Special attention has been paid to the design, for easy installation.

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS4392WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y4392WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS4392WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y4392WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT4352WM	220-240 V, 50/60 Hz AC	Lumi Test	1

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 23, 2024 | Source:
www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-line-midbay-emergency-lights



Product Code	Nominal Supply Voltage	Feature	Backup (h)
Y4352WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT4353WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y4353WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT4352WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y4352WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT4353WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y4353WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT4351WKH	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT4351WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y4351WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT4371W	24-230 V, 50/60 Hz AC, DC		
Y4371W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT4341WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 23, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-line-midbay-emergency-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com