

TRAIL: LINE MIDBAY



Teknoware Trail is an elegant emergency light that is easy to install on a lighting track. Thanks to its unique design, it is suitable for direct mounting on common lighting track systems. The luminaire can also be mounted directly on the ceiling. Trail has a modern and streamlined appearance so it blends in with the surroundings and architecture. Trail’s wide product family and range of optics offer many options to suit a variety of applications and systems.

Trail Line Midbay provides a long and narrow pattern that illuminates the escape routes efficiently.

for escape routes
self-contained or centrally supplied depending on model
installation: surface mounting on a lighting track (compatible with Global Trac and lighting trunking systems) or ceiling mounted
material: metal casing
colour: white (RAL 9003), other RAL-colours on request
SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSC492WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSC492WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 02, 2024 | Source: teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-line-midbay

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTC452WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTC453WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTC452WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWTC453WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTC451WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTC471W	24-230 V, 50/60 Hz AC, DC		