

TRAIL: ZONE LOWBAY



Teknoware Trail is an elegant emergency light that is easy to install on a lighting track. Thanks to its unique design, it is suitable for direct mounting on common lighting track systems. The luminaire can also be mounted directly on the ceiling. Trail has a modern and streamlined appearance so it blends in with the surroundings and architecture. Trail’s wide product family and range of optics offer many options to suit a variety of applications and systems.

Trail Zone Lowbay is particularly suitable for low spaces. The luminaire provides a broad, uniform light pattern that illuminates open areas efficiently.

for open areas
self-contained or centrally supplied depending on model
installation: surface mounting on a lighting track (compatible with Global Trac and lighting trunking systems) or ceiling mounted
material: metal casing
colour: white (RAL 9003), other RAL-colours on request
SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) | Form |
|--------------|------------------------|------------------|------------|------|
| TWSC292WM | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |
| TWSC292WMC | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: April 30, 2024 | Source: teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-zone-lowbay

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|---------------------------------|------------|
| TWSC292WA | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |
| TWSC292WAC | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|-----------|------------|
| TWTC252WM | 220-240 V, 50/60 Hz AC | Lumi Test | 1 |
| TWTC253WM | 220-240 V, 50/60 Hz AC | Lumi Test | 3 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|--------------------------|------------|
| TWTC252WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 1 |
| TWTC253WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 3 |

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature |
|--------------|----------------------------|---------------------------------------|
| TWTC251WK | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature | Form |
|--------------|---------------------------|---------|------|
| TWTC271W | 24-230 V, 50/60 Hz AC, DC | | |