


SMOOTH: ZONE



Teknoware Smooth is a small and elegant yet extremely durable emergency light optimised for outdoor use. The Smooth is a combination light, which you can use both as an emergency light and as a 300 lumen general light depending on the model. Because of the stylish design, the luminaire blends seamlessly into the architecture of the building. The Smooth always consists of two units: the luminaire and a separated indoor electronic unit. The Smooth includes a 5-metre fire-proof installation cable between the units. The luminaire is designed for surface mounting on a wall. The Smooth has an impact-resistant cast aluminium casing (IK10), and it is dust- and waterproof (IP65 for the visible part of the luminaire). The standard colour of the luminaire is graphite grey (RAL 7024), other colours are available on request (e.g. white RAL 9003).

The Smooth Zone is a compact emergency light designed to illuminate open areas efficiently. The luminaire provides a broad, even pattern.

for open areas

installation height: up to 4 metres, depending on model

self-contained or centrally supplied, depending on model

IP class: IP65 (for the visible part of the luminaire), IP20 (for the separate electronic unit)

installation: surface mounting on a wall (also requires installation of the separate electronic unit)

includes a 5-metre fire-proof installation cable between the units

material: cast aluminium (IK10)

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 06, 2024 | Source: teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/smooth-zone



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

colour: graphite grey (RAL 7024), other RAL-colours on request
SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER
CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSA892WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER
CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSA892WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND
SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTA853WMF	220-240 V, 50/60 Hz AC	Lumi Test	3
TWTA852WMF	220-240 V, 50/60 Hz AC	Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND
WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTA853WAF	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
TWTA852WAF	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTA851WK	220-240 V, 50/60 Hz AC,DC	Intelligent Controller, Tapsa Control

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTA841WK	24 V, 50/60 Hz AC, DC	Tapsa Control	