


SAFE 82 EMERGENCY LIGHTS



SAFE 82 is a high ceiling area LED emergency light, with ceiling and wall mounting as standard. SAFE 82 can be installed at a height of 4-20 meters.

SAFE 82 is particularly easy and quick to install thanks to a separate mounting plate.

SAFE 82 family of luminaires are splash water proof and suitable for damp areas and, for example, parking halls and outdoor roofed shelters.

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT8251WKH	220-240 V, 50/60 Hz AC, DC	Tapsa Control
Y8251WKH	220-240 V, 50/60 Hz AC, DC	Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT8251WH	220-240 V, 50/60 Hz AC, DC		
Y8251WH	220-240 V, 50/60 Hz AC, DC		

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 03, 2024 | Source: teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-82-emergency-lights