
ZONESPOT II: HIGHBAY, SURFACE-MOUNTED EMERGENCY LIGHTS







The Zonespot II Highbay is a surface-mounted emergency light that is particularly suitable for high spaces. The luminaire's optics are designed to provide a broad, uniform light pattern that illuminates open areas effectively.

Thanks to the IP44 enclosure class, the Zonespot II is also suitable for damp areas. The

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 06, 2024 | Source: teknoware.fi/en/emergency-lighting/emergencylights/emergency-light-product-families/zonespot-ii-highbay-surface-mounted-emergencylights



luminaire is easy and quick to install thanks to a separate mounting base, which is also connected to the power supply.

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) | Form |
|--------------|------------------------|------------------|------------|------|
| TWS8492WMCT | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |
| TWS8492WMC | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|---------------------------------|------------|
| TWS8492WACT | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |
| TWS8492WAC | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|-----------|------------|
| TWT8452WMT | 220-240 V, 50/60 Hz AC | Lumi Test | 1 |
| TWT8453WMT | 220-240 V, 50/60 Hz AC | Lumi Test | 3 |
| TWT8452WM | 220-240 V, 50/60 Hz AC | Lumi Test | 1 |
| TWT8453WM | 220-240 V, 50/60 Hz AC | Lumi Test | 3 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|---------------|------------|
| TWT8452WAT | 220-240 V, 50/60 Hz AC | Aalto Control | 1 |
| TWT8453WAT | 220-240 V, 50/60 Hz AC | Aalto Control | 3 |
| TWT8452WA | 220-240 V, 50/60 Hz AC | Aalto Control | 1 |
| TWT8453WA | 220-240 V, 50/60 Hz AC | Aalto Control | 3 |

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature |
|--------------|----------------------------|---------------------------------------|
| TWT8456WKT | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |
| TWT8456WK | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |
| Y8456WK | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved. Date: May 06, 2024 | Source: teknoware.fi/en/emergency-lighting/emergencylights/emergency-light-product-families/zonespot-ii-highbay-surface-mounted-emergencylights



We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 06, 2024 | Source: teknoware.fi/en/emergency-lighting/emergencylights/emergency-light-product-families/zonespot-ii-highbay-surface-mounted-emergencylights

