


# TKT41 CENTRAL BATTERY SYSTEMS



TKT41 series is an easy and inexpensive solution, for when you want to supply a relatively small number of luminaires in a limited area. The series also is suitable for premises, where the central battery system can be decentralized to several independent areas.

In TKT41xx there are, depending on the type, either 8 or 16 circuit outputs, which can be set in two circuit increments to either maintained or non-maintained.

## Technical data:

input voltage 230 VAC

output voltage main supply 24 VAC

output voltage battery supply 24 VDC

battery voltage 24 V is formed by two 12 V batteries connected in series

In TKT41xx there are 8 or 16 output circuits

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 28, 2024 | Source: [teknoware.fi/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt41-central-battery-systems](https://teknoware.fi/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt41-central-battery-systems)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](https://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



max 20 luminaires per circuit

NON-ADDRESSABLE 24 V CENTRAL BATTERY SYSTEMS

| Product Code | Nominal Supply Voltage     | Number of Output Circuits | Max Load of Circuits (VA) |
|--------------|----------------------------|---------------------------|---------------------------|
| TKT4144      | 1~ N/PE 220-240 VAC, 50 Hz | 8 x 120 VA / W            |                           |
| TKT4188      | 1~ N/PE 220-240 VAC, 50 Hz | 16 x 120 VA / W           |                           |