SOLID: LINE LOWBAY EMERGENCY LIGHTS















Solid Line Lowbay are designed for escape route emergency lighting. The luminaire is completely dust proof and water proof, so for example it is suitable for industrial premises, parking halls, as well as for outdoor use.

The Solid luminaire uses long-lasting LEDs as its light source.

Special attention has been paid to the design, for easy installation.

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS4292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y4292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS4292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y4292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 03, 2024 | Source: teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-line-lowbay-emergency-lights



Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT4252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y4252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT4253WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y4253WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT4252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y4252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT4253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y4253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT4251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y4251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT4271W	24-230 V, 50/60 Hz AC, DC		
Y4271W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT4241WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

